



| Specification | |
|----------------|---------------|
| Fluid | |
| Max. Press. | MPa |
| Max. Temp. | |
| Expansion Amt. | + 10, - 25 mm |

| | | | | | |
|-----|-----------------|-------------------|-------------|---------|------|
| 12 | Guide Pipe | Carbon Steel Tube | ガイドパイプ | STK | 1 |
| 11 | Shipping Bolt | Rolled Steel | SHIPPINGボルト | SS400 | 3set |
| 10 | Shipping Washer | Rolled Mild Steel | SHIPPING座金 | SPHC | 3 |
| 9 | Ring | Rolled Steel | リング | SS400 | 1 |
| 8 | Inside Pipe | Stainless Steel | 内筒 | SUS316L | 1 |
| 7 | Outside Pipe | Rolled Mild Steel | 外筒 | SPHC | 1 |
| 6 | Control Ring | Rolled Steel | コントロールリング | SS400 | 1set |
| 5 | Bellows | Stainless Steel | ベローズ | SUS316L | 1 |
| 4 | Ring | Rolled Steel | リング | SS400 | 1 |
| 3 | Guide Pipe | Carbon Steel Tube | ガイドパイプ | STK | 1 |
| 2 | Flange | Rolled Steel | フランジ | SS400 | 2 |
| 1 | Packing Seat | Stainless Steel | パッキンシート | SUS316L | 2 |
| No. | Name of Parts | Material | 部品名 | 材質 | Q.TY |

Shipping Washer, Shipping Bolt, piping (fixed points and guide installation) are to be removed after installation (fixing point and guide execution).
 Be sure to remove the Shipping Washer and Shipping Bolt after installation (Fixing point and guide execution).
 (mm)

| Size | L | 使用最大長さ Max.operating Length | 使用最小長さ Min.operating Length | 最大伸縮長さ Max.Expansion Length | Do | Flange JIS 20K RF | | | | | | Weight (kg) |
|------|-----|-----------------------------------|-----------------------------------|-----------------------------------|-------|-------------------|-----|-----|----|---|------|----------------|
| | | | | | | D | C | G | t | f | n-h | |
| 20A | 365 | 375 | 340 | 35 | 58.2 | 100 | 75 | 56 | 16 | 1 | 4-15 | 2.7 |
| 25A | 365 | 375 | 340 | 35 | 58.2 | 125 | 90 | 67 | 16 | 1 | 4-19 | 3.6 |
| 32A | 365 | 375 | 340 | 35 | 73.2 | 135 | 100 | 76 | 18 | 2 | 4-19 | 4.4 |
| 40A | 365 | 375 | 340 | 35 | 73.2 | 140 | 105 | 81 | 18 | 2 | 4-19 | 5.3 |
| 50A | 365 | 375 | 340 | 35 | 98.2 | 155 | 120 | 96 | 18 | 2 | 8-19 | 6.8 |
| 65A | 415 | 425 | 390 | 35 | 109.7 | 175 | 140 | 116 | 20 | 2 | 8-19 | 9.5 |
| 80A | 415 | 425 | 390 | 35 | 135.7 | 200 | 160 | 132 | 22 | 2 | 8-23 | 13.1 |
| 100A | 415 | 425 | 390 | 35 | 161.7 | 225 | 185 | 160 | 24 | 2 | 8-23 | 13.9 |

TYPE EB-11 EXPANSION JOINT 伸縮管継手

| | |
|-------------|--------------|
| Approval | M. Kume |
| Check | H. Tange |
| Drawing | T. Shinjo |
| Drawing No. | Y-0175-6010 |
| Date | 29 OCT. 2004 |

