

20K

Features

1. The main parts are mostly made with 13Cr stainless steel. Usable for hot fluids up to 350°C.
2. Support for special fluids by exchanging the packing, gasket and main parts. We also undertake maintenance using genuine parts at any time.

Product Types

Globe, Gate, Check, Needle, Y Globe, Bellows seal, Angle, Strainer, Ball, Strainer ball valves

Fluid • Temperature • Pressure

Unit: MPa

Service temperature limit by fluid (°C)		Steady water flow			Oil, air, steam, pulsating water						LPG		
		60	104	120	104	200	220	230	250	300	350	80	120
Globe	Standard, needle, Y, angle			2.75						2.26	1.96		
	PTFE disc											2.35	
	Bellows			2.50						2.26	1.96		
Gate	Standard, high temperature specification			2.75						2.26	1.96		
Check	Standard, screw-down stop check			2.75						2.26	1.96		
	PTFE disc											2.35	
Strainer	Standard			2.75						2.26	1.96		
	For LPG											2.35	
	Strainer ball											2.35	
Ball	For LPG											2.35	
	For general use		2.75		2.75	0.98		0.40	0				

*1 Heat-resistant coating is recommended in case the service temperature exceeds 120°C.

Test Pressure

Unit: MPa


Test description	Body pressure resistance		Valve seat leakage		Back seat leakage
	Water pressure	Air pressure	Water pressure	Air pressure	Air pressure
Globe, gate, check, angle, Y Globe valves	4.20		3.08		
Bellows seal valve		2.50		2.50	
Globe valve for LPG	3.60	2.64		2.64	2.64
Check valve for LPG/Ball/Strainer ball valve	3.60	2.64		2.64	
Strainer	4.20				
Ball valve for general use	4.20		3.08		

Product Code **M20KFT**

20K

Strainer Flanged

Product Name	Material	Remarks
Body	FCD-S	
Cover	FCD-S	
Screen	SUS304	50 mesh
Gasket	H1215	
Plug	S25C	



Nominal diameter (A)	10	15	20	25	32	40	50
L	120	130	140	160	190	210	250
H	57	68	77	91	137	154	170

20K

20K